

Facestock

A yellow, one side fluorescent coated woodfree paper.

| | | |
|--------------|---------------------|---------|
| Basis Weight | 73 g/m ² | ISO 536 |
| Caliper | 78 µm | ISO 534 |

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

Hygroflat 55, a one side coated, bleached kraft paper.

| | | |
|--------------|---------------------|---------|
| Basis Weight | 55 g/m ² | ISO 536 |
| Caliper | 58 µm | ISO 534 |

Laminate

| | | |
|---------------|------------|---------|
| Total Caliper | 152 µm±10% | ISO 534 |
|---------------|------------|---------|

Performance data

| | | |
|------------------------|---------------|--------------|
| Initial Tack | 17 N/25mm | FTM 9 Glass |
| Peel Adhesion 90° | 7 N/25mm | FTM 2 St.St. |
| Min. Application Temp. | 0 °C | |
| Service temperature | -20°C to 80°C | |

Adhesive Performance

The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

Applications and use

The product is ideal for applications where the vivid colours are used to distinguish products e.g. inventory labels, file labels, pallet labels etc. The well balanced laminate construction ensures optimum layflatness during conversion and end use for a wide range of conditions.

The hygroflat backing paper is specially suited to the more critical refolding demands of high-speed computer printers, providing optimum layflatness and excellent interfolding characteristics.

Conversion & printing

LASERCOPY RADIANTS are designed for the manufacturing of A4 sheets for use in; medium speed laser printers and laser printers, dry toner copiers. The facestock surface provides excellent toner anchorage and print resolution.

The Backing paper can be printed with conventional printing methods.

Special Approvals

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry, non fatty foodstuffs.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

aa378

Fasson®

LASERCOPY RADIANT YELLOW - S2012HTC-HF55



| | |
|--------------------------|---|
| LASERCOPY RADIANT YELLOW |  |
|--------------------------|---|

| | |
|----------|--|
| S2012HTC |  |
|----------|--|

| | |
|------|---|
| HF55 |  |
|------|---|

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000



Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be communicated to Avery Dennison within that time frame, Avery Dennison will evaluate and determine the existence of the defect and further decide, at its sole discretion, to either replace the defective product without charge or compensate it with a credit note in such amount as Avery Dennison deems reasonable. Avery Dennison shall have no responsibility beyond the replacement value of the defective product nor shall in any way be liable or responsible for consequential or incidental damages.

ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.