

Facestock

A white polyethylene film with a print-receptive topcoating.

Basis Weight	118 g/m ²	ISO 536
Caliper	120 µm	ISO 534

Adhesive

An extra permanent, acrylic based adhesive.

Liner

BG45 white, a supercalendered glassine paper.

Basis Weight	70 g/m ²	ISO 536
Caliper	61 µm	ISO 534
Transparency	50 %	DIN 53147

Laminate

Total Caliper	216 µm±10%	ISO 534
---------------	------------	---------

Performance Data

Initial Tack	24 N/25mm	FTM 9 Glass
Peel Adhesion 90°	16 N/25mm	FTM 2 St.St.
Min. Application Temp.	5 °C	
Service Temperature	-40 °C to 90 °C	

Adhesive Performance

S700 is a reinforced permanent acrylic based adhesive with very good initial tack and adhesion to a wide range of substrates.

Applications and Use

A robust film, allowing reliable dispensing of large labels and complex label shapes. Due to its flexibility, the product is suitable for squeezable bottles and other flexible containers.

Conversion and Printing

The modified acrylic based topcoating allows printing by the conventional printing technologies including letterpress, flexo, gravure and screen printing, giving good results with solvent, UV curing and water based inks. In case of solvent screen inks please consult your ink manufacturer


Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

AD267

Fasson ®

PE120 TOP WHITE S700 INC-BG45WH



PE120 TOP WHITE

S700

BG45WH

*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.
If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com*

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.