

Facestock

A semi-gloss white, one side coated, lightweight, calendered, woodfree printing paper.

The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

| | | |
|--------------|---------------------|--------------|
| Basis Weight | 62 g/m ² | ISO 536 |
| Caliper | 59 µm | ISO 534 |
| Fluorescence | >9 | Laetus Scale |

Adhesive

A special purpose permanent, rubber based adhesive for the pharmaceutical industry.

Liner

BG40 brown, supercalendered glassine paper.

| | | |
|--------------|---------------------|---------|
| Basis Weight | 55 g/m ² | ISO 536 |
| Caliper | 49 µm | ISO 534 |

Laminate

| | | |
|---------------|------------|---------|
| Total Caliper | 126 µm±10% | ISO 534 |
|---------------|------------|---------|

Performance Data

| | | |
|------------------------|-----------------|--------------|
| Initial Tack | 23 N/25mm | FTM 9 Glass |
| Peel Adhesion 90° | 12 N/25mm | 2TM 2 St.St. |
| Min. Application Temp. | 0 °C | |
| Service Temperature | -40 °C to 70 °C | |

Adhesive Performance

The adhesive S2060NP is suitable for pharmaceutical applications at low temperatures (around 5°C) and for secondary blood bag labelling. High initial tack and excellent adhesion on glass, PE, PP and cardboards.

Applications and Use

The flexible facestock allows application on small cylindrical containers, test tubes, curved substrates and on other known substrates in the pharmaceutical industry. The luminescent properties of the product allow automatic label dispensing and/or missing label control using UV-light detection equipment.

Own testing under practise conditions recommended.

Conversion and Printing

Excellent conversion characteristics in rotary and flat-bed. The double coated flexible paper allows fine-quality printing in letterpress, offset, flexo, screen, hot foil stamping and permits high quality printing of small typeface and difficult characters with optimum results

Compliance and Approvals

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assesment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs. It is in compliance with DIN ISO 3826 for secondary blood bag labelling.

AM226

Fasson®

LW FSC S2060NP-BG40BR IMP



LW FSC

S2060NP

BG40BR



The mark of
responsible forestry

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

The most recent cytotoxicity testing results obtained for S2060NP, concluded no relevant genotoxicity effect was observed; clearing the required ISO 10993-5 status. S2060NP complies with DIN ISO 3826-1.

S2060NP has a Drug Master File (DMF) submitted to the FDA. Letter of authorization can be issued on request.

To our best knowledge SVHC's are not part of the formulation of the product mentioned above and/or do not exceed the maximum concentration level of 0.1% by weight of the product.

This product is in compliance with the requirements of the European Union Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment, also known as "RoHS 2" or "RoHS recast".

S2060NP is covered by the Avery Dennison pharma change management programme. Please contact our technical representative to receive more information about our compliance statements and additional services

Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.