

Facestock

Acetate Satin Cloth is a white acetate satin fabric with high opacity and lustrous finish.

Basis Weight	125 g/m ²	ISO 536
Caliper	160 µm	ISO 534

Adhesive

A permanent, acrylic based adhesive.

Liner

BG45 white FSC is a supercalendered glassine paper.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight	71 g/m ²	ISO 536
Caliper	62 µm	ISO 534

Laminate

Total Caliper	255 µm±10%	ISO 534
---------------	------------	---------

Performance Data

Initial Tack	25 N/25mm	FTM 9 Glass
Peel Adhesion 90°	16 N/25mm	FTM 2 St.St.
Min. Application Temp.	5 °C	
Service Temperature	-40 °C to 90 °C	

Adhesive Performance

The adhesive is perfectly suitable for uses that need a good resistance to UV, fats or solvents. Good general adhesion performance on a wide range of substrates.

Applications and Use

Acetate Satin Cloth material is mainly used in attractive quality labels including conference badges, promotional stickers etc.

Conversion and Printing

Acetate Satin Cloth has very good printing properties for letterpress, flexo and offset processing. Apply a thin ink coating only. For letterpress use the lowest possible pressure. For screen printing a fine screen mesh is recommended.

Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

AU514

Fasson®

ACETATE SATINCLOTH S697-BG45WH FSC



ACETATE SATINCLOTH WHITE	
-----------------------------	--------------------------------------------------------------------------------------

S697	
------	---------------------------------------------------------------------------------------

BG45WH FSC	
------------	---------------------------------------------------------------------------------------



The mark of
responsible forestry

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000



Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2022 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.